

II. Amendments to the Claims

This listing of claims will replace all prior versions, and listings of claims in the application:

1. (Currently Amended) A portable toilet shelter comprising:

a base; and

a loop enclosure circumscribing said base, said loop enclosure

comprising:

opposed ~~longitudinally~~ planar non-foldable end walls, each end wall having longitudinally oriented opposed side edges;

opposed ~~longitudinally~~ planar non-foldable side walls between said ~~longitudinally~~ planar non-foldable opposed end walls, each of said ~~longitudinally~~ planar non-foldable side walls having longitudinally oriented opposed side edges; and

means for movably connecting said longitudinally oriented opposed side edges of said ~~longitudinally~~ planar non-foldable side walls to said longitudinally oriented opposed side edges of said end walls such that said opposed ~~longitudinally~~ planar non-foldable end walls and said opposed ~~longitudinally~~ planar non-foldable side walls complete said loop enclosure;

said portable toilet shelter being in a partially disassembled folded state when said loop enclosure is collapsed, wherein one each of said opposed ~~longitudinally~~ planar non-foldable end walls is in direct contact with at least a portion of a respective one of said ~~longitudinally~~ planar non-foldable side walls, said loop enclosure being collapsible to a stackable folded flat state having a thickness one each of said ~~longitudinally~~ planar non-

foldable end walls and one each of said ~~longitudinally~~ planar non-foldable side walls for transporting said portable toilet shelter;

said portable toilet shelter being in a partially erected state when said ~~longitudinally~~ planar non-foldable end walls are in an unfolded position respectively away from said ~~longitudinally~~ planar non-foldable side walls and said loop enclosure is in an upright and self-supporting position, wherein said ~~longitudinally~~ planar non-foldable side walls are substantially parallel to one another and said ~~longitudinally~~ planar non-foldable end walls are also substantially parallel to one another, such that said ~~longitudinally~~ planar non-foldable side walls are substantially transverse to said ~~longitudinally~~ planar non-foldable end walls.

2. (Currently Amended) The portable toilet shelter as claimed in claim 1, wherein said means for movably connecting comprises at least one flexible hinge fastened to respective longitudinally oriented side edges of said ~~longitudinally~~ planar non-foldable end and ~~longitudinally~~ planar non-foldable side walls.

3. (Currently Amended) The portable toilet shelter as claimed in claim 2, wherein said at least one flexible hinge is riveted to respective longitudinally oriented side edges of said ~~longitudinally~~ planar non-foldable end and ~~longitudinally~~ planar non-foldable side walls.

4. (Withdrawn) The portable toilet shelter as claimed in claim 2, further comprising:

a roof hingedly connected to one of said walls; and

a floor hingedly connected to one of said walls.

5. (Original) The portable toilet shelter as claimed in claim 1, further comprising a commode mounted to said base within said loop enclosure.

6. (Cancelled)

7. (Currently Amended) A portable toilet shelter comprising:

a base; and

a loop enclosure circumscribing said base, said loop enclosure comprising:

~~longitudinally~~ planar non-foldable front and ~~longitudinally~~ planar non-foldable back end walls, each of said ~~longitudinally~~ planar non-foldable front and back end walls having disposed thereon opposed longitudinally oriented side edges, opposed longitudinal ends, and an inward surface;

opposed ~~longitudinally~~ planar non-foldable side walls between said ~~longitudinally~~ planar non-foldable front and ~~longitudinally~~ planar non-foldable back end walls, each of said ~~longitudinally~~ planar non-foldable side walls having disposed thereon opposed longitudinally oriented side edges, opposed longitudinal ends, and an inward surface; and

a plurality of flexible hinge strips connecting said longitudinally oriented side edges of said ~~longitudinally~~ planar non-foldable side walls to respectively adjacent edges of said longitudinally oriented side edges of said ~~longitudinally~~ planar non-foldable front and ~~longitudinally~~ planar non-foldable back end walls such that said ~~longitudinally~~ planar non-foldable end walls and said ~~longitudinally~~ planar non-foldable side

walls complete said loop enclosure and said longitudinal oriented side ends of said ~~longitudinally~~ planar non-foldable end walls and said ~~longitudinally~~ planar non-foldable side walls collectively define opposed longitudinal oriented corner ends of said loop enclosure;

said loop enclosure being collapsible to a stackable folded flat state having a thickness of about one each of said ~~longitudinally~~ planar non-foldable front and [n] ~~longitudinally~~ planar non-foldable [e] back end walls and one each of said ~~longitudinally~~ planar non-foldable side walls for transporting said toilet shelter;

whereby one of said plurality of flexible hinge strips connected to said ~~longitudinally~~ planar non-foldable front end wall is foldable to move said planar non-foldable front end wall against a respective one of said ~~longitudinally~~ planar non-foldable side walls and further whereby another of said plurality of flexible hinge strips connected to said ~~longitudinally~~ planar non-foldable back end wall is foldable to move said planar non-foldable back end wall against a respective other of said ~~longitudinally~~ planar non-foldable side walls to collapse said loop enclosure, further whereby said ~~longitudinally~~ planar non-foldable front and ~~longitudinally~~ planar non-foldable back end walls are unfoldable respectively away from said ~~longitudinally~~ planar non-foldable side walls such that said loop enclosure is self-supporting when placed on one end of said opposed longitudinal ends thereof.

8. (Currently Amended) The portable toilet shelter as claimed in claim 7, wherein said plurality of flexible hinge strips are riveted to respective opposed edges of said ~~longitudinally~~ planar non-foldable front and ~~longitudinally~~ planar non-foldable back end walls and said ~~longitudinally~~ planar non-foldable side walls.

9. (Withdrawn) The portable toilet shelter as claimed in claim 7, further comprising:

- a roof hingedly connected to one of said walls; and
- a floor hingedly connected to one of said walls.

10. (Original) The portable toilet shelter as claimed in claim 7, further comprising a commode mounted to said base within said loop enclosure.

11. (Cancelled)

12. (Currently Amended) A portable toilet shelter comprising:

- a base;
- a loop enclosure circumscribing said base, said loop enclosure being foldable to a collapsed condition and unfoldable to a self-supporting condition, said loop enclosure comprising:

- a planar front end wall having disposed thereon left and right edges, top and bottom longitudinal ends, and an inward surface, said planar front end wall further having a door opening therethrough;

- an oppositely disposed planar back end wall having disposed thereon left and right edges, top and bottom longitudinal ends, and an inward surface;

- a planar right side wall between said planar front end and planar back end walls, said planar right side wall having disposed thereon opposed front and back edges, top and bottom longitudinal ends, and an inward surface;

a planar left side wall between said planar front end and planar back end walls, said planar left side wall having disposed thereon opposed front and back edges, top and bottom longitudinal ends, and an inward surface;

said longitudinal ends of said planar side and planar end walls collectively define longitudinal ends of said loop enclosure;

a plurality of flexible hinge strips, said plurality of hinge strips connecting said right edge of said planar front panel to said front edge of said planar right side wall, said back edge of said planar right side wall to said right edge of said planar back end wall, said left edge of said planar back end wall to said back edge of said planar left side wall, and said front edge of said planar left side wall to said left edge of said planar front wall, thereby completing said loop enclosure;

said loop enclosure being collapsible to a stackable folded flat state having a thickness of about one each of said planar front and planar back end walls and one each of said planar right and planar left side walls for transporting said portable toilet shelter₁;

whereby said planar front and planar back end walls are foldable with respect to each other ~~respectively~~ toward said side walls such that said inside surfaces of said planar front and planar back end walls respectively overlay said inside surfaces of said planar right and planar left side walls to collapse said loop enclosure, and further whereby said planar front and planar back end walls are unfoldable respectively away from said planar right and planar left side walls such that said loop enclosure is self-supporting when placed on one end of said opposed longitudinal ends thereof; and

a roof mounted to the other of said longitudinal ends of said loop enclosure.

13. (Previously Presented) The portable toilet shelter as claimed in claim 12, wherein said plurality of flexible hinge strips are riveted to respective edges of said planar end and side walls.

14. (Withdrawn) The portable toilet shelter as claimed in claim 12, further comprising:

a roof hingedly connected to one of said walls; and

a floor hingedly connected to one of said walls.

15. (Original) The portable toilet shelter as claimed in claim 12, further comprising a commode mounted to said base within said loop enclosure.

16. (Cancelled)

17. (Previously Presented) A portable toilet shelter adapted to be collapsed to facilitate transportation thereof, said portable toilet shelter having a base and a roof, said portable toilet shelter further comprising:

a substantially loop-like enclosure circumscribing said base, said substantially loop-like enclosure being divided into four substantially equal longitudinally oriented upright sections; and

a plurality of hinge members, one of said plurality of hinge members being interposed each of said four substantially equal longitudinally oriented upright sections;

said loop-like enclosure being collapsible to a stackable folded flat state having a thickness of about two of said four substantially equal longitudinally oriented upright sections for transporting said portable toilet shelter;

whereby when said portable toilet shelter is collapsed, two of said four substantially equal longitudinally oriented upright sections are in side by side relationship disposed atop another two of said four substantially equal longitudinally oriented upright sections, such that an increased number of said portable toilet shelters may be transported when in said collapsed state.

18. (Withdrawn) The portable toilet shelter as claimed in claim 17, further comprising:

a roof hingedly connected to said substantially loop-like enclosure; and

a floor hingedly connected to said substantially loop-like enclosure.

19. (Withdrawn) A flip-top toilet unit adapted for use with a portable toilet shelter, said flip-top toilet comprising:

a tank portion; and

a lid portion hingedly connected to said tank portion to close tank portion.

20. (Withdrawn) The flip-top toilet unit as claimed in claim 19, further comprising a toilet seat mounted to said lid portion.

21. (Original) A portable toilet shelter comprising:

a base; and

a loop enclosure circumscribing said base, said loop enclosure comprising:

opposed non-foldable planar end walls, each end wall having longitudinally oriented opposed side edges;

opposed non-foldable planar side walls between said non-foldable planar opposed end walls, each of said planar side walls having longitudinally oriented opposed side edges; and

means for connecting said longitudinally oriented opposed side edges of said planar side walls to said longitudinally oriented opposed side edges of said planar end walls such that said planar end walls and said planar side walls complete said loop enclosure, said means for connecting comprising a plurality of flexible hinge strips;

said portable toilet shelter being in a partially disassembled folded state when said loop enclosure is collapsed, wherein said planar end walls are in a folded position respectively against said planar side walls, such that each of said planar end walls is in direct contact with a respective one of said planar side walls, said loop enclosure being collapsible to a stackable folded flat state having a thickness of one each of said end walls and one each of said side walls for transporting said portable toilet shelter, said flat state defining an upper planar surface comprised of an outer surface of a planar end wall and an outer surface of a planar side wall with one of said plurality of flexible hinge strips attached to each longitudinal opposed side edges of each of said walls, said one of said plurality of flexible hinge strips attached to each opposed side edges of each said wall in said folded flat state whereby a

second collapsed loop enclosure laid on said folded flat state of said loop enclosure maintains a substantially horizontally disposed stackable position;

said portable toilet shelter being in a partially erected state when said planar end walls are in an unfolded position respectively away from said planar side walls and said loop enclosure is in an upright and self-supporting position, wherein said planar side walls are substantially parallel to one another and said planar end walls are also substantially parallel to one another, such that said planar side walls are substantially transverse to said planar end walls.